

TESTA MOBILE ROBE COLOR WASH 575



The ColorWash 575E AT Zoom is an electronic ballast version of ColorWash 575 AT Zoom, which provides flicker-free operation. The fixture offers an extremely smooth linear motorized zoom that ranges from 8 to 50°. Thanks to the zoom this fixture is ideal for all types of professional installations.

Source

- * Lamp: Compact high-pressure metal halide lamp
- * Base: GX-9.5
- * Approved model: Philips MSR 575/2
- * Control: Automatic and remote on/off
- * Ballast: Electronic

Optical System

- * High luminous-efficiency glass reflector
- * Two fresnel lenses of diameters 150 and 200 mm

Electrical Specification

- * Wiring options: EU model - 208/230/240V AC, 50/60Hz, US model - 100/120/208/230/240V AC, 50/60Hz
- * Power consumption: 720VA at 230V/50Hz

Mechanical Specification

- * Height: 588 mm (23.1") - head in horizontal position
- * Width: 470 mm (18.5")
- * Depth: 446 mm (17.6")
- * Weight: EU model - 31 kg (68.3 lbs), US model - 34.5 kg (76.1 lbs)

Thermal

- * Maximum ambient temperature (Ta): 40°C (104°F)
- * Maximum surface temperature: 80°C (176°F)

Control and Programming

- * Protocol: USITT DMX-512
- * Control channels: 16/18/19/21
- * DMX channels: 4 protocol modes
- * Stand-alone operation
- * Flicker-free operation
- * 3-editable programs, each up to 99 steps
- * Built-in demo sequences
- * Display: 4-digit LED display



- * *Pan/Tilt resolution: 16-bit*
- * *Colour wheel positioning: 8- or 16-bit*
- * *Zoom: 8- or 16-bit*
- * *Dimmer: 8- or 16-bit*
- * *Movement control: Tracking and vector*
- * *Built-in analyzer for easy fault finding*
- * *Data in/out: Locking 3-pin & 5-pin XLR*

Electromechanical Effects

- * *Cyan: 0 - 100%*
- * *Magenta: 0 - 100%*
- * *Yellow: 0 - 100%*
- * *CTO: 0 - 100%*
- * *Colour wheel: 5 replaceable "SLOT&LOCK" colours + open*
- * *Dimmer/Shutter: Full range dimming and variable strobe effect*
- * *Zoom: 8 - 50°*
- * *Pan: 530°*
- * *Tilt: 280°*

Rigging

- * *Mounting points: 4 pairs of 1/4-turn locks*
- * *2x Omega bracket with 1/4-turn quick locks*

Optional Accessories

- * *Module of Front wide-angle lens D200 (87° angle)*

